

Model : **FSB-880M-A10-VE**

ITEM	P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1	1907880002	PCB.FWB-880.Rev.A1.0.6Layers Green	HIPER	1907880002	E224709
2	1651612990	(TF)ZIF LGA 775 SKT.SMD.775P.FOXCONN.PE07 7527-1041-01	FOXCONN	PE077527-1041-01	E93750,
3	1752311000	PolySwitch.6V.1.1A.(Max 40A).Raychem.miniSMDC110-2	Raychem	miniSMDC110-2	E74889(S),
4	1651203291	IC SKT PLCC.SMD.32P(9P*7P).PRECI- DIP.540-99-032-17-400	PRECI-DIP	540-99-032-17-400	E107536(M) UL94V-0,
5	1655424020	(TF)ATX POWER CONNECTOR.12P*2.180D(M).DI P.凱迅.1121-700-24S	CATCH	1121-700-24S	E132701 UL94V-0,
6	1655404020	(TF)ATX POWER CONNECTOR.2P*2.180D.DIP.凱 迅.1121-700-04S	CATCH	1121-700-04S	E132701 UL94V-0,
7	1750119013	Battery.DIP.3V.RAYOVAC.BR23 35T3L	RAYOVAC	BR2335T3L	MH12542,
8	1759100002	Buzzer.DIP.40mA.85dB P- P=6.5mm.志豐.KC-1206	KINGSTATE	KC-1206	E194246 UL94V-2,
9	1653002100	(TF)PIN HEADER.2*1P.180D.(M).2.54mm .DIP	JIH VEI	21B12564- XXS10B-01G-6/3	E107536 UL94V-0,
10	1654816200	USB CONNECTOR QUAD PORT.16P.90D(M).Techbest.KS- 004-ATB-10	Techbest	KS-004-ATB-10	E107536(M) UL94V-0
11	1653005200	PIN HEADER.5*2P.180D.(M).2.54mm .DIP.何迪.201-2*NGS(R)	HO-BASE	201-2*NGS(R)	E107536(M) UL94V-0,
12	1653005205	PIN HEADER.5*2P.180D.(M).W/O PIN9 2.0mm.DIP.何迪.209-	HIO-BASE	209-2X5GS W/O 9	E107536(M) UL94V-0,
13	165440910B	D-SUB CONNECTOR.9P.90D(M).DIP.Gr een.Astron.DB6A-09-AMGN1T	Astron	DB6A-09-AMGN1T	UL94V-0,
14	1653205203	(TF)BOX HEADER.5*2P.180D.(M).2.0mm. DIP.凱迅.1147-000-10S	CATCH	1147-000-10S	E132701 UL94V-0 ,
16	16515C0494	(TF)DDR2 SKT.DIP.240P.(Blue).SPEED TECH.P90-P11-3018	SPEED TECH	P90-P11-3018	E44716 UL94V-0,

17	16515C0493	(TF)DDR2 SKT.DIP.240P.(Black).SPEED TECH.P90-P11-1018	SPEED TECH	P90-P11-1018	E44716 UL94-V0,
18	'1655004014	(TF)WAFER.4P.180D.(M).2.54m m.DIP.凱迅.1190-700-042	CATCH	1190-700-042	E132701 UL94V-0
19	1655003010	(TF)WAFER.3P.180D.(M).2.54m m.DIP.凱迅.1190-700-03S	CATCH	1190-700-03S	E119177(M) UL94V-0,
20	1653217205	(TF)BOX HEADER.17*2P.180D.(M).2.54m m.DIP W/O PIN5.凱迅.1137-000- 34SA	CATCH	1137-000-34SA	E107536A UL94V- 0,
21	1653004200	PIN HEADER.4*2P.180D.(M).2.54mm .DIP.何迪.201-2*NGS(R)	HO-BASE	201-2*NGS(R)	E107536(M) UL94V-0,
22	1653300100	MINI JUMPER.(YELLOW).何 迪.206-BY	HO-BASE	206-BY	E107536(M) UL94V-0,
23	1654282202	SLOT PCI EXPRESS.82*2P.180D(F).DIP.TE CHBEST.WPCS-	TECHBEST	WPCS- 164AN1B22UWL	E164708(S) UL94V-0
24	1653220208	(TF)BOX HEADER.20*2P.180D.(M).2.54m m.DIP W/O PIN20(Blue).凱 迅.1137-020-40SA	CATCH	1137-020-40SA	E107536(A) UL94V-0,
25	1653006101	PIN HEADER.6*1P.180D.(M).2.0mm. DIP.何迪.2000-1WS-6	HO-BASE	2000-1WS-6	E107536(M) UL94V-0,
26	1654612304	MINI DIN.6/6P.90D(F).DIP.Kb/Ms for PC99 CONNECTOR.康	CONTeK	MZL266102G401	E130155(M) UL94V-0,
27	'1652508212	PHONE JACK.8P.90D.(F).RJ45 W/Transformer & LED.BOTHHAND.LU1T516-43	BOTHHAND	LU1T516-43	E105888 UL94V- 0,E174837,E13015 5(M) UL94V- 0,E56742,E201362 UL94V-0,
28	1654425302	(TF)D-SUB CONNECTOR.25P.90D(F).DIP.F OXCONN.DM11351-PR3-4F	FOXCONN	DM11351-PR3-4F	E205196 UL94V- 0,E59481 UL94V- 0,
29	1211100662	(TF)COIL.0.6uH.DIP Wire Size 1.1*2mm.2wire 35.TRIO.PSG- 1410-R60M1	TRIO	PSG-1410-R60M1	E85640,E201757,
30	1211101161	COIL.1.1uH.DIP Wire Size 2.3mm.35材 3wire 30Amp.三集 瑞.TCU-5035B-1R1M-02	TRIO	TCU-5035B-1R1M-	E201575,E85640,E 180908,E35586,

31	1211101264	(TF)COIL.1.2uH.20%.DIP Wire Size.1.8mm 18材 3wire 20Amp.TRIO.LG-12AM11C03	TRIO	LG-12AM11C03	E85640,E35586,E201757,E180908,
32	1654260201	SLOT.60*2P.180D.(F).DIP.FOXC ONN.EH06001-CAW	FOXCONN	EH06001-CAW	E59481 E54352 E54700,
33	1654907003	(TF)SATA CONNECTOR.7P.180D(M).DIP.B LUE.TECHBEST.161S01-029(A)-	TECHBEST	161S01-029(A)-L	E130155(M) UL94V-0,
34	1654907002	(TF)SATA CONNECTOR.7P.180D(M).DIP.T ECHBEST.161S01-025A	TECHBEST	161S01-025A	E204143 UL94V-0,
35	1654515308	(TF)D-SUB H/D CONNECTOR.15P.90D.(F).Blue. DIP.凱迅.3125-000-15SB	CATCH	3125-000-15SB	E107536(M) UL94V-0,
43	1709070800	SATA CABLE.7P Pitch 1.27mm.80cm.W/Lock	Alphaplus	CB-AA-0006	E177865,E107536 (M) UL94V-0
44	1701100305	Flat Cable.9P/DB9P MALE.10P/2.0mm Pitch/IDC NO FOLD.30cm.W/BACKET	CATCH	A002-014	UL2651,E72332,E107536(M) UL94V-0,E209329 ULVW-1,E107536(M) UL94V-0,E212834,E56070 (S)
45	1701400453	Cable.40P 2.54mm IDC W/Nose W/Fold.40P 2.54mm IDC W/Nose W/Fold.45cm.Blue ATA-100.凱迅.B016-009-2	CATCH	B016-009-2	UL2678,E101344(S),
46	1701340704	Flat Cable.34P.70cm.GRAY for FDD	CATCH	A003-246	E107536(M) UL94V-0,UL2651 VW-1,
47	1759200161	(TF)CPU Cooler Fan.for LGA775 Pentium4 3.6G.4P.12V.Dual ball bearing.米倫.LGA-775-91502	ML	LGA-775-91502	E236658,