

Model : HSB-660I-A10

ITEM	P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1	1701340702	Flat Cable.34P.70cm.GRAY 5.25"&3.5"FDD P-2.0mm.何迪	HO-BASE	@1701340702	UL2651 VW-1,E107536(M) UL94V-
2	1701400453	Cable.40P 2.54mm IDC W/Nose W/Fold.40P 2.54mm IDC W/Nose W/Fold.45cm.Blue ATA-100.凱迅.B016-009-2	CATCH	B016-009-2	UL2678,E101344(S),
3	1701010302	Flat Cable.1S/1P.D-SUB W/BRACKET 26-25 10-9 2P	HO-BASE CATCH	@1701010302 A002-015	UL2651,E107536(M) UL94V-0,UL2651 VW-1,E144392 UL94V-0,E107536(M)
4	1700060192	(TF)Cable.6P-6P-6P.19cm.IVORY PS2/KB&Mouse	HO-BASE CATCH	@1700060192 A003-114	E119932(S), E107536(M) UL94V-0, UL2725,UL2464, E107536(M) UL94V-0,
5	1709100201	(TF)Usb Cable.20cm2.0mm.W/Bracket	CATCH Vso	1709100201 AUS15-008S0-002	E35586(S),E101344 VW-1,E107536(M) UL94V-0,E209436,E107536(M) UL94V-0 ,
6	1709140301	Cable.Phone Jack*3&14P 2.0mm Housing.DB9P(M) 10P 2.0mm IDC.2.54mm Housing 4P.30cm.W/Backet	CATCH	A003-160	E144392 UL94V-0,E54979 VW-1SC,E209329 VW-1,E107536(M) UL94V-0,
7	1653925216	Compact Flash Header.25*2P.90D.SMD.1.27m pitch.for TypeII.SPEED TECH.N016-0140-004	SPEED TECH	N016-0140-004	E192672 UL94V-0,
8	1752001600	(TF)FUSE.SMD.6V.1.1A.1206.Littlefuse.1206L110WRT	Littlefuse	1206L110WRT	E183209 ,
9	1759100006	Buzzer.SMD.3.3V.80mA.90dB.KINGSTATE.KSS-J4D20	KINGSTATE	KSS-J4D20	E194246 UL94V-2
10	1651203291	IC SKT PLCC.SMD.32P(9P*7P).PRECI-DIP.540-99-032-17-400	PRECI-DIP	540-99-032-17-400	E107536(M) UL94V-0,
11	1653013202	(TF)PIN HEADER.13*2P.180D.(M).2.0mm.SMD.W/Cap.Astron.27-24041-213-1G-TB1-R	Astron	27-24041-213-1G-TB1-R	E52579(M) UL94V-0,E52579(M) UL94V-0,
12	1653017201	(TF)PIN HEADER.17*2P.180D.(M).2.0mm.SMD.W/Cap.Astron.27-24041-217-1G-TB1-R	Astron	27-24041-217-1G-TB1-R	E52579(M) UL94V-0,
13	1653005202	(TF)PIN HEADER.5*2P.180D.(M).2.0mm.SMD.W/CAP.Astron.27-24041-205-1G-TB1-R	Astron	27-24041-205-1G-TB1-R	E52579(M) UL94V-0,

14	'1654020000	Board-Wire Connector.20P.180D(M).SMD.Pitch=1.25mm W/ Reinforcement.Hirose.DF13-20DP-1.25V	Hirose	DF13-20DP-1.25V	E172082(M) UL94V-0,
15	'1654040000	Board-Wire Connector.40P.180D(M).SMD.Pitch=1.25mm W/ Reinforcement.Hirose.DF13-40DP-1.25V	Hirose	DF13-40DP-1.25V	E172082(M) UL94V-0,
16	'1653007204	(TF)PIN HEADER.7*2P.180D.(M).2.0mm.SMD.W/Cap.Astron.27-24041-207-1G-TB1-R	Astron	27-24041-207-1G-TB1-R	E52579(M) UL94V-0,E52579(M) UL94V-0,
17	1907660I01	PCB.HSB-660I.Rev.A1.0.8Layers Green	HIPER	1966041A	E224709 UL94V-0,
18	1750119011	(TF)BATTERY.3V.200mA.SO NY.CR2032	SONY	CR2032	MH12566,
19	1653900034	Compact Flash Header.1.27mm.Ejector for Type II.SPEED TECH.N003-	SPEED TECH	N003-0011-100	E192672 UL94V-0,
20	1653220208	(TF)BOX HEADER.20*2P.180D.(M).2.54mm.DIP W/O PIN20(Blue).凱迅.1137-020-40SA	CATCH	1137-020-40SA	E107536(A) UL94V-0,
21	1655420020	(TF)ATX POWER CONNECTOR.10P*2.180D.DIP.凱迅.1121-700-20S	CATCH	1121-700-20S	E132701 UL94V-0,
22	1652512200	PHONE JACK.12P.90D.(F) DIP.RJ45 with LED.FOXCONN.JM37115-L1	FOXCONN	JM37115-L1	E93750(S), UL94V-0,
23	1653005100	PIN HEADER.5*1P.180D.(M).2.54mm.DIP.何迪.205-1*XGS	HO-BASE	205-1*XGS SERIES	E107536(M) UL94V-0,
24	1653132220	PCB SKT.32*2P.180D.(F).Holder=11.00mm P=2.30mm.DIP.凱迅.1232-251-64	CATCH	1232-251-64	E107536A UL94V-0,
25	1653120225	PCB SKT.20*2P.180D.(F).Holder=11.00mm P=2.30mm.DIP.凱迅.1232-251-40	CATCH	1232-251-40	E107536A UL94V-0,
26	1655304020	(TF)WAFER BOX.4P.180D.(M).2.0mm.W/L OCK DIP.凱迅.1192-700-04S	CATCH	1192-700-04S	E132701 UL94V-0,
27	1655003010	(TF)WAFER.3P.180D.(M).2.54mm.DIP.凱迅.1190-700-03S	CATCH	1190-700-03S	E119177(M) UL94V-0,
28	'1653006101	PIN HEADER.6*1P.180D.(M).2.0mm.DIP.何迪.2000-1WS-6	HO-BASE	2000-1WS-6	E107536(M) UL94V-0,

29	'1655005021	(TF)WAFER BOX.5P.180D.(M).2.5mm.W/L OCK.DIP.何迪.2503-WS-5	HO-BASE	2503-WS-5	E53898 UL94V- 0,E44716 UL94V-2,
30	'1654606303	MINI-DIN Receptacle.6P.90D.(F).DIP Slim Type.CANNON.PDMLD-060-0	CANNON	PDMLD-060-0	E52579(M) UL94V- 0,
31	'1651584490	DIMM SKT.DIP.168P.(DRST2*84S1G RC01Z51).FOXCONN.AT0840 1-D2	FOXCONN	AT08401-D2	E93750,UL94V-0,
32	'1653003201	PIN HEADER.3*2P.180D.(M).2.0m m.DIP.何迪.2000-2WS-2*3	HO-BASE	2000-2WS-2*3	E107536(M) UL94V- 0,Housing UL94V-1,
33	1653003101	PIN HEADER.3*1P.180D.(M).2.0m m.DIP.何迪.2000-1WS-3	HO-BASE	2000-1WS-3	E107536(M) UL94V- 0,
34	'1653005200	PIN HEADER.5*2P.180D.(M).2.54 mm.DIP.何迪.201-2*NGS(R)	HO-BASE	201-2*NGS(R)	E107536(M) UL94V- 0,
35	1211100105	(TF)COIL.1uH.DIP Pinlength=3.0mm.Wire Size 1.2mm.52材 1Wire*4 10Amp. 震元.TC5052N-1R0M-UL	AG	TC5052N-1R0M- UL	E197768,E203950,
36	1211102560	(TF)COIL.2.5uH.DIP.Pinlength =3.0mm.Wire Size 0.7*3Pmm.52材 3Wire*8 30Amp.震元.TC5052N-2R5M-	AG	TC5052N-2R5M- UL	E197768,E203950,
37	'1653300102	(TF)MINI JUMPER.2.0mm.(BLACK).何 迪.MJ-2.0B	HO-BASE	MJ-2.0B	E59481 UL94V-0,
38	1651607921	ZIF SKT.DIP.370Pin.PGA GOLD FLASH.AMP.2-916783-	AMP	2-916783-8	E28476,
39	1961558000	Heat sink.36*36*15mm.for SBC-558.BLACK.益聿	INVIN	1961558000	MH13556
40	1654415304	D-SUB CONNECTOR.15P.90D(F).DIP. BLUE.何迪.01CD-15F3N	HO-BASE	01CD-15F3N	E107536(M) UL94V- 0,
41	1653004302	(TF)PIN HEADER.3*4P.180D.(M).2.0m m.DIP.Astron.27-2103-403-1G-	Astron	27-2103-403-1G- R	E52579(M) UL94V- 0,E109088(M) UL94V-0,