

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1214309002	(TF)Common Choke.4P.90 Ohm(100Mhz) 2.0*1.2mm SMD.永馳.YFD2012T#900S	YOUTH	YFD2012T#900S	E84081(S),
1653002100	(TF)PIN HEADER.2*1P.180D.(M).2.54mm.DIP	JVE	21B12504- XXS10B-01G-6/2	E107536 UL94V-0,
1653005200	(TF)PIN HEADER.5*2P.180D.(M).2.54mm.DIP	JVE	21B22564- XXS10B-01G-6/3-VXX	E107536 UL94V-0,
1654232200	(TF)SLOT.64P.180D.(F).PCI-E X4 DIP.FOXCONN.2EG03217-D2D-DF	FOXCONN	2EG03217-D2D-DF	E172082,
1654249205	(TF)SLOT PCI EXPRESS.49*2P.180D(F).DIP.Foxconn.2EG04917-D2D-	Foxconn	2EG04917-D2D-DF	E172082,
1654260207	(TF)SLOT.60*2P.180D.(F).DIP.FOXCONN.EH06001-HHW-DF	FOXCONN	EH06001-HHW-DF	E172082,E93750,
1654282202	(TF)SLOT PCI EXPRESS.82*2P.180D(F).DIP.TECHBEST.WPCS-164AN1B22UWL	TECHBEST	WPCS-164AN1B22UWL	E164708(S) UL94V-0,
1654282204	(TF)SLOT PCI EXPRESS.82*2P.180D(F).DIP.FOXCONN.2EG08217-D2D-DF	FOXCONN	2EG08217-D2D-DF	E172082,
1654907003	(TF)SATA CONNECTOR.7P.180D(M).DIP.BLUE.TECHBEST.161S01-029A-L	TECHBEST	161S01-029A-L	E130155(M) UL94V-0,
1655003120	(TF)Wafer.3P.90D.(M).W/LOCK.2.54mm.致威.24W1160-03R10-01T	JVE	24W1160-03R10-01T	E48674 UL94V-2,
1655005021	(TF)WAFER BOX.5P.180D.(M).2.5mm.W/LOCK.DIP.HO-BASE.2503-WS-5	HO-BASE	2503-WS-5	E53898 UL94V-0,E44716 UL94V-2,
1655005121	(TF)WAFER BOX.5Pin.90D.(M).Pitch=2.5mm.W/LOCK DIP.JIH VEI.24W1171-05R10-01T	JVE	24W1171-05R10-01T	E44716,
1655008120	(TF)WAFER BOX.8Pin.90D.(M).Pitch=2.5mm.W/LOCK DIP.JIH VEI.24W1171-08R10-01T	JVE	24W1171-08R10-01T	E44716,
1655408020	(TF)ATX POWER CONNECTOR.4P*2.180D.DIP.CATCH.1121-700-08S	CATCH	1121-700-08S	E53898,
1655424020	(TF)ATX POWER CONNECTOR.12P*2.180D(M).DIP.凱迅.1121-700-24S	CATCH	1121-700-24S	E132701 UL94V-0,
1656304022	(TF)HOUSING.4P.180D.(M).5.08mm.W/O LOCK.何迪.5082A-WS-4	HO-BASE	5082A-WS-4	E53898 UL94V-0,E44716 UL94V-2,
1752310000	(TF)PolySwitch.8V.1.1A(Max 40A).TYCO.miniSMDC110F-2	TYCO	miniSMDC110F-2	E74889,
1907206032	(TF)PCB.BP-206SH-P3.Rev.A1.0.4Layers Green.PICMG1.3	EVERLAST WIN		E216522 V-0