

TF-COM-965-A10

Date:2008/07/22

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1211000180	(TF)COIL.1uH.+/- 20%.SMD.7.3*6.8*3.0mm.DCR=9mohm.Irms=1 1Amp.GOTREND.GSTC063P-1R0MN	GOTREND	GSTC063P-1R0MN	E84081,
1211101064	(TF)COIL.1uH.20%.SMD.11.5x10.5x4.0mm.DC R=3m ohm.Irms=18Amp.GOTREND.GSTC104P- 1R0MN	GOTREND	GSTC104P-1R0MN	E218438 / E84081,
1211105673	(TF)COIL.0.56uH.Irms=25A.Isat=40A.20%.SM D(11.5x10.3x4.0).2pin.RDC=1.8m Ohm.GOTREND.GSTC104P-R56MN	GOTREND	GSTC104P-R56MN	E218438 , E84081,
1600000203	(TF)SWITCH.SMD.2S SPST.HCH.HDS402-E	HCH	HDS402-E	E172082(M),E102861,
1651611993	(TF)ZIF mPGA478M SKT.SMD.W/O A1&B1.478P.For Merom.FOXCON.PZ4782A- 274M-01	FOXCON	PZ4782A-274M-01	E93750,
1655902122	(TF)WAFER BOX.2Pin.90D.(M).Pitch=1.25mm.SMD.CATC H.1201-700-02RM	CATCH	1201-700-02RM	E119177(M),
1907965003	(TF)PCB.COM-965.Rev.A1.0.8Layers Green			E224709 94V-0,
121110336B	(TF)COIL.3.3uH.+/- 20%.DCR=0.034Ohm.Idc=3A.SMD.5.8*5.2*4.5 mm.GOTREND.GSDR54P-3R3M	GOTREND	GSDR54P-3R3M	E218438,E84081,
121110336L	(TF)COIL.3.3uH.SMD.7.3*6.8*3.0mm.DCR=28 m ohm.Irms=6Amp.GOTREND.GSTC063P-	GOTREND	GSTC063P-3R3MN	E84081,
16515A099B	(TF)DDR2 SODIMM SKT.SMD.H=5.2mm.200P.REVERSE.FOXCO NN.AS0A426-N2RN-4F	FOXCONN	AS0A426-N2RN-4F	E93750,
16515A099C	(TF)DDR2 SODIMM SKT.SMD.H=9.2mm.200P.REVERSE.FOXCO NN.AS0A426-NARN-4F	FOXCONN	AS0A426-NARN-4F	E93750,
165300420L	(TF)PIN HEADER.4*2P.180D.(M).1.27mm.SMD.W/Cap .Astron.27-44041-204-2G-TB1R	Astron	27-44041-204-2G-TB1R	E52579(M) 94V-0,
16540M0001	(TF)Board to Board connector.220P.180D(M).SMD.Pitch=0.5mm.FO XCONN.QT012206-1031-8F	FOXCONN	QT012206-1031-8F	E54705,