

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1211000180	(TF)COIL.1uH.+/- 20%.SMD.7.3*6.8*3.0mm.DCR=9mohm.Irms=11Amp .GOTREND.GSTC063P-1R0MN	GOTREND	GSTC063P-1R0MN	E84081,
1211100102	(TF)INDUCTOR.1uH.10%.SMD 0805 DCR=0.45 ohm IDC=50mA.GOTREND.GBL201209P-1R0K	GOTREND	GBL201209P-1R0K	
121110226C	(TF)COIL.2.2uH.SMD.7.3*6.8*3.0mm.+/- 20%.DCR=18mohm.Irms=8Amp.GOTREND.GSTC06 3P-2R2MN	GOTREND	GSTC063P-2R2MN	E218438/E840 81/E174837,
121110336L	(TF)COIL.3.3uH.SMD.7.3*6.8*3.0mm.DCR=28m ohm.Irms=6Amp.GOTREND.GSTC063P-3R3MN	GOTREND	GSTC063P-3R3MN	E84081,
1600010203	(TF)SWITCH.SMD.2S SPST.HCH.HDS502-E	HCH	HDS502-E	E41797/E4792 4/E194582,
16515A0999	Phase out,(TF)DDR2 SODIMM SKT.SMD.H=5.2mm.200P.1.8V.FOXCONN.AS0A42 6-N2SN-4F	FOXCONN	AS0A426- N2SN-4F	E93750,
16515A099A	Phase out,(TF)DDR2 SODIMM SKT.SMD.H=9.2mm.200P.1.8V.FOXCONN.AS0A42 6-NASN-4F	FOXCONN	AS0A426- NASN-4F	E93750,
1651900860	(TF)IC SKT.SMD.8Pin.SOIC.LOTES.ACA-SPI-004- K01	LOTES	ACA-SPI-004- K01	E57552,
165300420L	(TF)PIN HEADER.4*2P.180D.(M).1.27mm.SMD.W/Cap.Astro n.27-44041-204-2G-TB1R	Astron	27-44041-204- 2G-TB1R	E52579(M) 94V-0,
16540M0001	(TF)Board to Board connector.220P.180D(M).SMD.Pitch=0.5mm.FOXCO NN.QT012206-1031-2H	FOXCONN	QT012206- 1031-2H	E54705,
1655902122	(TF)WAFER BOX.2Pin.90D.(M).Pitch=1.25mm.SMD.CATCH.120 1-700-02RM	CATCH	1201-700- 02RM	E119177(M),
1655903122	(TF)WAFER BOX.3Pin.90D.(M).Pitch=1.25mm.SMD.CATCH.120 1-700-03RM	CATCH	1201-700- 03RM	E119177(M),
1655906121	(TF)WAFER BOX.6P.90D.(M).1.0mm.W/LOCK.SMD.E-Call.0110- 01-532-060	E-Call	0110-01-532- 060	E179987,
1907LUNA03	(TF)PCB.COM-LUNA.Rev.A1.0.8Layers Green.(Thickness:2.0mm)	ALLIED CIRCUIT		E171522