

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1211000180	(TF)COIL.1uH.+/-20%.SMD.7.3*6.8*3.0mm.DCR=9mohm.Irms=11Amp.GOTREND.GSTC063P-1R0MN	GOTREND	GSTC063P-1R0MN	E84081,
1211103370	(TF)COIL.0.33uH.Irms=20A.Isat=30A.20%.SMD(7.3x6.8x3.0).2pin.RDC=3.9m Ohm.GOTREND.GSTC063P-R33MN	GOTREND	GSTC063P-R33MN	E218438 / E84081,
1211106872	(TF)COIL.0.68uH.SMD.7.3*6.8*3.0mm.+/-20%.DCR=5mohm.Irms=15.5Amp.GOTREND.GSTC063P-R68MN	GOTREND	GSTC063P-R68MN	E214423,
1600030203	(TF)SWITCH.SMD.2S SPST.HCH.HPS602-E	HCH	HPS602-E	E41938,E41797,
1651900860	(TF)IC SKT.SMD.8Pin.SOIC.LOTES.ACA-SPI-004-K01	LOTES	ACA-SPI-004-K01	E57552,
1654930305	(TF)FPC/FFC Connector.30P.90D(F).SMD.Pitch 0.5mm.E-call Enterprise.0951-01-109-300	E-call Enterprise	0951-01-109-300	E1799987,
1655902130	(TF)WAFER BOX.2P.90D.(M).1.0mm.SMD.CATCH.1204-700-02RM	CATCH	1204-700-02RM	E52579(M),
1655903122	(TF)WAFER BOX.3Pin.90D.(M).Pitch=1.25mm.SMD.CATCH.1201-700-03RM	CATCH	1201-700-03RM	E119177(M),
121110100F	(TF)Inductor.10uH.10%.SMD.2.4*1.6mm.GOTREND.GNLE2012P-100K	GOTREND	GNLE2012P-100K	E84081,
16515A099X	Phase out, 替代料 16515A2994,(TF)DDR3 SODIMM SKT.SMD.H=9.2mm.204P.STANDARD.1.5V.FOXCONN.AS0A626-JASG-7H	FOXCONN	AS0A626-JASG-7H	E54705,

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
16515A099Z	Phase out, 替代料 16515A2992,(TF)DDR3 SODIMM SKT.SMD.H=5.2mm.204P.STANDARD.1.5V.FOXCONN.AS0A626-N2SN-7H	FOXCONN	AS0A626-N2SN-7H	E54705,
165300420L	(TF)PIN HEADER.4*2P.180D.(M).1.27mm.SMD.W /Cap.Astron.27-44041-204-2G-TB1R	Astron	27-44041-204-2G-TB1R	E52579(M) 94V-0,
16540M0001	(TF)Board to Board connector.220P.180D(M).SMD.Pitch=0.5mm.FOXCONN.QT012206-1031-2H	FOXCONN	QT012206-1031-2H	E54705,
1907QM5724	(TF)PCB.COM-QM57_HM55.Rev.A1.1_0_0.12Layers Green.Thickness=2.0mm	ALLIED CIRCUIT		E171522,