

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1211000180	(TF)COIL.1uH.+/- 20%.SMD.7.3*6.8*3.0mm.DCR=9mohm.Irms=1 1Amp.GOTREND.GSTC063P-1R0MN	GOTREND	GSTC063P-1R0MN	E84081,
121110336L	(TF)COIL.3.3uH.SMD.7.3*6.8*3.0mm.DCR=28 m ohm.Irms=6Amp.GOTREND.GSTC063P-	GOTREND	GSTC063P-3R3MN	E84081,
121110336P	(TF)COIL.3.3uH.± 20%.SMD.4.5x4x2mm.DCR=89.3m ohm.Idc=2.7Amp.VISHAY.IHLP1616BZER3R3 M11	VISHAY	IHLP1616BZER3R3M11	E32638,
1600000203	(TF)SWITCH.SMD.2S SPST.HCH.HDS402-E	HCH	HDS402-E	E172082(M),E10 2861,
16515A099B	(TF)DDR2 SODIMM SKT.SMD.H=5.2mm.200P.REVERSE.1.8V.FO XCONN.AS0A426-N2RN-4F	FOXCONN	AS0A426-N2RN-4F	E93750,
1653003202	(TF)PIN HEADER.3*2P.180D.(M).2.0mm.SMD.W/Cap. Astron.27-24041-203-1G-TB1-R	Astron	27-24041-203-1G-TB1-R	E52579 UL94V- 0,E391376 UL94V-0,
1653300102	(TF)MINI JUMPER.2.0mm.(BLACK)	1=>HO-BASE 2=>JVE	1=>MJ-2.0B 2=>27S1001- OPS35-01G	E59481 UL94V- 0,E248993 UL V94-0/E107536,
16540M0001	(TF)Board to Board connector.220P.180D(M).SMD.Pitch=0.5mm.F OXCONN.QT012206-1031-8F	FOXCONN	QT012206-1031-8F	E54705,
1655902122	(TF)WAFER BOX.2Pin.90D.(M).Pitch=1.25mm.SMD.CATC H.1201-700-02RM	CATCH	1201-700-02RM	E119177(M),
1655902130	(TF)WAFER BOX.2P.90D.(M).1.0mm.SMD.CATCH.1204- 700-02RM	CATCH	1204-700-02RM	E52579(M),
1907MENL03	(TF)PCB.COM-U15.Rev.A1.0.8 Layers Green	ALLIED CIRCUITS		E171522