

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1211101066	(TF)COIL.1.0uH.± 20%.SMD.4.5x4x2mm.DCR=27m ohm.Idc=4.5Amp.VISHAY.IHLP1616BZER1R0M1 1	VISHAY	IHLP1616BZER 1R0M11	E32638,
1600010203	(TF)SWITCH.SMD.2S SPST.HCH.HDS502-E	HCH	HDS502-E	E41797/E47924/ E194582,
1653002204	(TF)PIN HEADER.2*2P.180D.(M).2.00mm.SMD.W/Cap.凱 迅.1140-010-04MP	CATCH	1140-010-04MP	E52579(M) UL94V-0,
1653003202	(TF)PIN HEADER.3*2P.180D.(M).2.0mm.SMD.W/Cap.Astr on.27-24041-203-1G-TB1-R	Astron	27-24041-203- 1G-TB1-R	E52579 UL94V- 0,E391376 UL94V-0,
1653300102	(TF)MINI JUMPER.2.0mm.(BLACK)	1=>HO-BASE 2=>JVE	1=>MJ-2.0B 2=>27S1001- OPS35-01G	E59481 UL94V- 0,E248993 UL V94-0/E107536,
1655902122	(TF)WAFER BOX.2Pin.90D.(M).Pitch=1.25mm.SMD.CATCH.12 01-700-02RM	CATCH	1201-700-02RM	E119177(M),
1655902130	(TF)WAFER BOX.2P.90D.(M).1.0mm.SMD.CATCH.1204-700- 02RM	CATCH	1204-700-02RM	E52579(M),
121110226C	(TF)COIL.2.2uH.SMD.7.3*6.8*3.0mm.+/- 20%.DCR=18mohm.Irms=8Amp.GOTREND.GSTC 063P-2R2MN	GOTREND	GSTC063P- 2R2MN	E218438/E84081 /E174837,
121110336L	(TF)COIL.3.3uH.SMD.7.3*6.8*3.0mm.DCR=28m ohm.Irms=6Amp.GOTREND.GSTC063P-3R3MN	GOTREND	GSTC063P- 3R3MN	E84081,
121110336P	(TF)COIL.3.3uH.± 20%.SMD.4.5x4x2mm.DCR=89.3m ohm.Idc=2.7Amp.VISHAY.IHLP1616BZER3R3M1 1	VISHAY	IHLP1616BZER 3R3M11	E32638,

TF-COM-U15-A20

DATE: 6-Aug-10

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
16515A099B	Phase out,(TF)DDR2 SODIMM SKT.SMD.H=5.2mm.200P.REVERSE.1.8V.FOXCONN.AS0A426-N2RN-4F	FOXCONN	AS0A426-N2RN-4F	E93750,
16540M0001	(TF)Board to Board connector.220P.180D(M).SMD.Pitch=0.5mm.FOXCONN.QT012206-1031-2H	FOXCONN	QT012206-1031-2H	E54705,
1907MENL06	(TF)PCB.COM-U15.Rev.A2.0.8Layers Green(HDI).Thickness=1.6mm	ALLIED CIRCUIT		E171522,