

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1211000180	(TF)COIL.1uH.+/- 20%.SMD.7.3*6.8*3.0mm.DCR=9mohm.Irms=11Amp. GOTREND.GSTC063P-1R0MN	GOTREND	GSTC063P-1R0MN	E84081,
1211101064	(TF)COIL.1uH.20%.SMD.11.5x10.3x4.0mm.DCR=3m ohm.Irms=18Amp.GOTREND.GSTC104P-1R0MN	GOTREND	GSTC104P-1R0MN	E218438 / E84081,
121110336L	(TF)COIL.3.3uH.SMD.7.3*6.8*3.0mm.DCR=28m ohm.Irms=6Amp.GOTREND.GSTC063P-3R3MN	GOTREND	GSTC063P-3R3MN	E84081,
1211105673	(TF)COIL.0.56uH.Irms=25A.Isat=40A.20%.SMD(11.5x 10.3x4.0).2pin.RDC=1.8m	GOTREND	GSTC104P-R56MN	E218438 , E84081,
1315970211	(TF)PWR.SMD.SOT-25 1.1A.High-Side Switch wit Flag.RICHTEK.RT9702A-PB	RICHTEK	RT9702A-PB	E219878,
16515A0996	(TF)DDR2 SODIMM SKT.SMD.200P.H=6.5mm.FOXCONN.AS0A426-	FOXCONN	AS0A426-N6SN-4F	E93750,
16515A0997	(TF)DDR2 SODIMM SKT.SMD.200P.H=6.5mm.FOXCONN.AS0A426-	FOXCONN	AS0A426-N6RN-4F	E93750,
1651611993	(TF)ZIF mPGA478M SKT.SMD.W/O A1&B1.478P.For Merom.FOXCON.PZ4782A-274M-	FOXCON	PZ4782A-274M-01	E93750,
1652510202	(TF)PHONE JACK.10P.90D.(F).RJ45 W/Transformer & LED.BOTHHAND.LA1T109D-A-D43 LF	BOTHHAND	LA1T109D-A-D43 LF	E174837,E22 1000,E59481, E130155,
1653003100	(TF)PIN HEADER.3*1P.180D.(M).2.54mm.DIP	Astron	27-01031XX-1G Series	E107536 UL94V-0,
1653003101	(TF)PIN HEADER.3*1P.180D.(M).2.0mm.DIP	JVE	21B12050-XXS10B-01G-4/2.8	E107536 UL94V-0,
1653004200	(TF)PIN HEADER.4*2P.180D.(M).2.54mm.DIP	JVE	21B22564-XXS10B-01G-6/3-VXX	E107536 UL94V-0,
1653005201	(TF)PIN HEADER.5*2P.180D.(M).2.0mm.DIP	JVE	21B22050-XXS10B-01G-4/2.8	E107536 UL94V-0,
1653005205	(TF)PIN HEADER.5*2P.180D.(M).W/O PIN9 2.0mm.DIP	1=>JVE 2=>HO- BASE	1=>21N22050- 10S10B-01G- 4/2.8-V1-G 2=>@16530052 05	E54695,E525 79,
1653006101	(TF)PIN HEADER.6*1P.180D.(M).2.0mm.DIP	JVE	21B12050-XXS10B-01G-4/2.8	E107536 UL94V-0,
1653205203	(TF)BOX HEADER.5*2P.180D.(M).2.0mm.DIP.CATCH.1147-	CATCH	1147-000-10S	E132701 UL94V-0 ,
1653213203	(TF)BOX HEADER.13*2P.180D.(M).2.0mm.DIP.凱 迅.1147-000-26S	CATCH	1147-000-26S	E132701 UL94V-0 ,
1653217205	(TF)BOX HEADER.17*2P.180D.(M).2.54mm.DIP W/O PIN5.凱迅.1137-000-34SA	CATCH	1137-000-34SA	E107536A UL94V-0,
1653220208	(TF)BOX HEADER.20*2P.180D.(M).2.54mm.DIP W/O PIN20(Blue).凱迅.1137-020-40SA	CATCH	1137-020-40SA	E107536(A) UL94V-0,
1653300100	(TF)MINI JUMPER.(YELLOW)	JVE	27S1002- OPS60B-01G-Y	E107536(M) UL94V- 0,E59481,

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1653300102	(TF)MINI JUMPER.2.0mm.(BLACK)	1=>HO-BASE 2=>JVE	1=>MJ-2.0B 2=>27S1001-OPS35-01G	E59481 UL94V-0,E248993 UL V94-0/E107536,
1653925216	(TF)Compact Flash Header.25*2P.90D.SMD.1.27mm pitch.for TypeII.SPEED TECH.N016@0140-104+N01P4011-0099	SPEED TECH	N016@0140-104-	E192672,
1654030003	(TF)Board-Wire Connector.30P.180D(M).SMD.Pitch=1.25mm.W/Reinfo rcem.E-call.0110-01-553-300	E-call	0110-01-553-300	E113875,
1654515308	(TF)D-SUB H/D CONNECTOR.15P.90D.(F).Blue.DIP.凱迅.3125-000-15SB	CATCH	3125-000-15SB	E107536(M) UL94V-0,
1654606200	(TF)MINI DIN RECEPT TABLE.6P.90D.(F).W/SPRING	CONTEK	MAN3061F1G401	E130155(M) 94V-0,
1654804100	(TF)USB CONNECTOR SINGLE PORT.Upright.4P.90D(M).HO-BASE.KS-001V-ANW	HO-BASE	KS-001V-ANW	E52579(M),
1654907002	(TF)SATA CONNECTOR.7P.180D(M).DIP.TECHBEST.161S01-	TECHBEST	161S01-025A	E204143 UL94V-0,
1655003010	(TF)WAFER.3P.180D.(M).2.54mm.DIP.CATCH.1190-700-03S	CATCH	1190-700-03S	E119177(M) UL94V-0,
1655003022	(TF)WAFER BOX.3P.180D.(M).2.5mm.W/LOCK DIP.凱迅.1191-700-03S	CATCH	1191-700-03S	E119177(M) UL94V-0 ,
1655005021	(TF)WAFER BOX.5P.180D.(M).2.5mm.W/LOCK.DIP.HO-BASE.2503-WS-5	HO-BASE	2503-WS-5	E53898 UL94V-0,E44716 UL94V-2,
1655305020	(TF)WAFER BOX.5P.180D.(M).2.0mm.W/LOCK DIP.CATCH.1192-700-05S	CATCH	1192-700-05S	E132701 UL94V-0,
1655404020	(TF)ATX POWER CONNECTOR.2P*2.180D.DIP.凱迅.1121-700-04S	CATCH	1121-700-04S	E132701 UL94V-0,
1655420020	(TF)ATX POWER CONNECTOR.10P*2.180D.DIP.CATCH.1121-700-20S	CATCH	1121-700-20S	E132701 UL94V-0,
1700060192	(TF)Cable.6P-6P-6P.19cm.IVORY PS2/KB&Mouse	1=>CATCH 2=>HO-BASE	1=>A003-114 2=>@1700060192	E119932(S), E107536(M) UL94V-0, UL2725,UL2464, E107536(M) UL94V-0,

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1701100305	(TF)Flat Cable.9P/DB9P MALE.10P/2.0mm Pitch/IDC NO FOLD.30cm.W/BRACKET	CATCH	A002-014	UL2651,E72332,E107536(M) UL94V-0,E209329 ULVW-1,E107536(M) UL94V-0,E212834,E56070(S) UL94HB,E186230,
170110030A	(TF)Flat Cable.9P DB9P MALE.10P 2.00mm Pitch IDC.30cm.w/o Fold, w/ Bracket PCI-675F	CATCH	A003-051	E72332,E107536(M) UL94V-0,
1701260307	(TF)Flat Cable.9P/DB9P MALE&25P DB25P FEMALE.10P 2mm&26P 2mm/IDC NO FOLD.30cm.W/BKT.凱迅.A002-015	CATCH	A002-015	UL2651 VW-1,E72332,E107536(M) UL94V-0,
1701340704	(TF)Flat Cable.34P.70cm.GRAY for FDD	CATCH	A003-246	E107536(M) UL94V-0,UL2651 VW-1,
1701400453	(TF)Cable.40P 2.54mm IDC W/Nose W/Fold.40P 2.54mm IDC W/Nose W/Fold.45cm.Blue ATA-100	CATCH	B016-009-2	E107536(M) 94V-0,E101344,
1703030501	(TF)Wire.3P 2.5mm Housing.3P 2.5mm Housing.50cm	CATCH	A003-232	E170689 VW-1,E41797(M), E144392 UL94V-0,E108485(S) VW-1,E132701 VW-1,E108485(S) ULVW-1,E191023,
1709070800	(TF)SATA CABLE.7P Pitch 1.27mm.80cm.W/Lock	1=>Alphaplus 2=>CATCH	1=>CB-AA-0006 2=>A003-569	E177865,E107536 UL94V-0 ,E107536(M), E96118,

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1709100201	(TF)Usb Cable.20cm2.0mm.W/Bracket	CATCH	1709100201	E107536/E206838/E188601/E56118/E97527,E209436,E107536(M)UL94V-0 ,
175011901H	(TF)Lithium	PANASONIC	CR2032	MH12210,
1750220323	(TF)Battery Holder.CR2032 DIP.Straight.LOTES.KB7566BP5L	LOTES	KB7566BP5L	E135714 V-0,
1752001601	(TF)FUSE.SMD.6V.1.1A.1206.Littlefuse.1206L110WR	Littlefuse	1206L110WR	E183209,
175910000B	(TF)BUZZER.DIP.80mA.85dB(P-P=4mm).ADVANCED ACOUSTIC.AC-903Q-P2-LF	ADVANCED ACOUSTIC	AC-903Q-P2-LF	E45587,
1759281301	(TF)CPU Cooler Fan.(+12V).PushPin.for HSB-813S.CMT.P-m906P	CMT	P-m906P	E41938/E236658,
1907965P01	(TF)PCB.HSB-965P.Rev.A1.0.8Layers Green	K-BRIDGE		E120558,
9657666600	(TF)Accessory.for All Series Jumper	CATCH	9657666600	E107536(M)94V-0,
9681666600	(TF)Cable ASSY.for SBC Series	CATCH	A003-252	E144392UL94V-0,E108485(S)VW-1,E132701VW-1,
M10810A000	(TF)METAL.AL.Heat sink.For HSB-810A 37.5*37.5*20mm.兎軒.SPR373721A	SPRING SPREAD	SPR373721A	E96144,