

| P/N        | DESCRIPTION                                                                                                     | MAKER                | PART NO.                                             | UL NO./ Flame                   |
|------------|-----------------------------------------------------------------------------------------------------------------|----------------------|------------------------------------------------------|---------------------------------|
| 1211100109 | (TF)INDUCTOR.1uH.10%.SMD 1210<br>DCR=0.08 ohm IDC=1.5A.高創.GNLC-3225P-                                           | GOTREND              | GNLC-3225P-1R0K                                      | E75077(S),                      |
| 1211101264 | (TF)COIL.1.2uH.20%.DIP Wire Size.1.8mm 18<br>材 3wire 20Amp.TRIO.LG-12AM11C03                                    | TRIO                 | LG-12AM11C03                                         | E85640,E35586,<br>E201757,E1809 |
| 1211105673 | (TF)COIL.0.56uH.Irms=25A.Isat=40A.20%.SM<br>D(11.5x10.3x4.0).2pin.RDC=1.8m<br>Ohm.GOTREND.GSTC104P-R56MN        | GOTREND              | GSTC104P-R56MN                                       | E218438 ,<br>E84081,            |
| 1211105674 | (TF)COIL.0.56uH.20%.DIP.35A.GOTREND.G<br>MAT-131210-P-R56-M                                                     | GOTREND              | GMAT-131210-P-R56-M                                  | E218438 /<br>E84081,            |
| 1214309006 | (TF)Common Choke.4P.90<br>Ohm(100Mhz).2.0*1.2mm                                                                 | GOTREND              | GTHW2012PE-900T                                      | E218438 /<br>E84081,            |
| 1315970110 | (TF)PWR.SMD.SOT-25 High-Side<br>Switch.RICHTEK.RT9701PBL                                                        | RICHTEK              | RT9701PBL                                            | E219878,                        |
| 1651612992 | (TF)ZIF LGA 775<br>SKT.SMD.775P.FOXCONN.PE077526-1041-0D                                                        | FOXCONN              | PE077526-1041-0D                                     | E93750,                         |
| 1652522206 | (TF)PHONE JACK.22P.90D.(F).RJ45+USB<br>Stack 2.0.w/LED.LAN-<br>10/100.FOXCONN.JFM24U1B-21U6-4F                  | FOXCONN              | JFM24U1B-21U6-4F                                     | E93750,                         |
| 1653002100 | (TF)PIN HEADER.2*1P.180D.(M).2.54mm.DIP                                                                         | JVE                  | 21B12564-XXS10B-01G-                                 | E107536<br>UL94V-0,             |
| 1653004200 | (TF)PIN HEADER.4*2P.180D.(M).2.54mm.DIP                                                                         | JVE                  | 21B22564-XXS10B-01G-                                 | E107536<br>UL94V-0,             |
| 1653005200 | (TF)PIN HEADER.5*2P.180D.(M).2.54mm.DIP                                                                         | JVE                  | 21B22564-XXS10B-01G-                                 | E107536<br>UL94V-0,             |
| 1653005205 | (TF)PIN HEADER.5*2P.180D.(M).W/O PIN9<br>2.0mm.DIP                                                              | 1=>HO-BASE<br>2=>JVE | 1=>1053005205<br>2=>21N22050-10S10B-01G-<br>408-V1-G | E54695,E52579,                  |
| 1653006101 | (TF)PIN HEADER.6*1P.180D.(M).2.0mm.DIP                                                                          | JVE                  | 21B12050-XXS10B-01G-                                 | E107536<br>UL94V-0,             |
| 1653205203 | (TF)BOX HEADER.5*2P.180D.(M).2.0mm.DIP.<br>凱迅.1147-000-10S                                                      | CATCH                | 1147-000-10S                                         | E132701<br>UL94V-0 ,            |
| 1653217205 | (TF)BOX<br>HEADER.17*2P.180D.(M).2.54mm.DIP W/O                                                                 | CATCH                | 1137-000-34SA                                        | E107536A<br>UL94V-0,            |
| 1653220208 | (TF)BOX<br>HEADER.20*2P.180D.(M).2.54mm.DIP W/O                                                                 | CATCH                | 1137-020-40SA                                        | E107536(A)<br>UL94V-0,          |
| 1653300100 | (TF)MINI JUMPER.(YELLOW)                                                                                        | JVE                  | 27S1002-OPS60B-01G-Y                                 | E107536(M)<br>UL94V-            |
| 1653302150 | (TF)JUMPER WIRE.1*2P.180D.2.54mm DIP<br>for 845e Heat sink                                                      | JVE                  | 21N12564-03A10B-01G-                                 | E107536(M)<br>UL94V-            |
| 1653900034 | (TF)Compact Flash Header.1.27mm.Ejector for<br>Type II.SPEED TECH.N003@0011-100                                 | SPEED<br>TECH        | N003@0011-100                                        | E192672,235269<br>9(E),         |
| 1653925216 | (TF)Compact Flash<br>Header.25*2P.90D.SMD.1.27mm pitch.for<br>TypeII.SPEED TECH.N016@0140-<br>104-N01P4011-0099 | SPEED<br>TECH        | N016@0140-104+N01P4011-0099                          | E192672,                        |
| 1654232200 | (TF)SLOT.64P.180D.(F).PCI-E X4<br>DIP.FOXCONN.2EG03217-D2D-DF                                                   | FOXCONN              | 2EG03217-D2D-DF                                      | E172082,                        |
| 1654260207 | (TF)SLOT.60*2P.180D.(F).DIP.FOXCONN.EH0<br>6001-HHW-DF                                                          | FOXCONN              | EH06001-HHW-DF                                       | E172082,E9375<br>0,             |

| P/N        | DESCRIPTION                                                                               | MAKER                    | PART NO.                     | UL NO./ Flame                                                       |
|------------|-------------------------------------------------------------------------------------------|--------------------------|------------------------------|---------------------------------------------------------------------|
| 1654282202 | (TF)SLOT PCI EXPRESS.82*2P.180D(F).DIP.TECHBEST.WP CS-164AN1B22UWL                        | TECHBEST                 | WPCS-164AN1B22UWL            | E164708(S) UL94V-0,                                                 |
| 1654425302 | (TF)D-SUB CONNECTOR.25P.90D(F).DIP.FOXCONN.DM11351-H5W3-4F                                | FOXCONN                  | DM11351-H5W3-4F              | E205196 / E107536,                                                  |
| 1654515308 | (TF)D-SUB H/D CONNECTOR.15P.90D.(F).Blue.DIP.凱                                            | CATCH                    | 3125-000-15SB                | E107536(M) UL94V-0,                                                 |
| 1654612307 | (TF)MINI DIN.6/6P.90D(F).DIP.Kb/Ms for PC99 CONNECTOR.Foxconn.MH11061-P36-4F              | Foxconn                  | MH11061-P36-4F               | E154352,E59481,E93750,                                              |
| 1654808304 | (TF)USB CONNECTOR DUAL PORT.8P.90D.(F).for                                                | CONTEK                   | UFL2443-F1-01                | E130155(M) UL94V-0,                                                 |
| 1654907002 | (TF)SATA CONNECTOR.7P.180D(M).DIP.TECHBEST.161S01-025A                                    | TECHBEST                 | 161S01-025A                  | E204143 UL94V-0,                                                    |
| 1655004014 | (TF)WAFER.4P.180D.(M).2.54mm.DIP.CATCH.1190-700-042                                       | CATCH                    | 1190-700-042                 | E132701 UL94V-0 ,                                                   |
| 1655404020 | (TF)ATX POWER CONNECTOR.2P*2.180D.DIP.凱迅.1121-700-                                        | CATCH                    | 1121-700-04S                 | E132701 UL94V-0,                                                    |
| 1655424020 | (TF)ATX POWER CONNECTOR.12P*2.180D(M).DIP.凱迅.1121-                                        | CATCH                    | 1121-700-24S                 | E132701 UL94V-0,                                                    |
| 1701100305 | (TF)Flat Cable.9P/DB9P MALE.10P/2.0mm Pitch/IDC NO FOLD.30cm.W/BRACKET                    | CATCH                    | A002-014                     | UL2051,E172552 ,E107536(M) UL94V-0,E209329 ULVW-1,E107536(M) UL94V- |
| 1701340704 | (TF)Flat Cable.34P.70cm.GRAY for FDD                                                      | CATCH                    | A003-246                     | E107536(M) UL94V-                                                   |
| 1701400453 | (TF)Cable.40P 2.54mm IDC W/Nose W/Fold.40P 2.54mm IDC W/Nose                              | CATCH                    | B016-009-2                   | E107536(M) 94V-0,E101344,                                           |
| 1709070800 | (TF)SATA CABLE.7P Pitch 1.27mm.80cm.W/Lock                                                | 1=>CATCH<br>2=>Alphaplus | 1=>A003-569<br>2=>CB-AA-0006 | E177805,E107536 UL94V-0 ,E107536(M),E96118                          |
| 1709100204 | (TF)USB Cable.5P*2 2.54 Pitch.20cm.Normal W/Bracket                                       | CATCH                    | A003-056                     | E101344 VW-1,E107536(M) UL94V-0,                                    |
| 1750220320 | (TF)Battery                                                                               | LOTES                    | KB6615BP5L                   | E59481,                                                             |
| 1752310000 | (TF)PolySwitch.8V.1.1A(Max 40A).TYCO.miniSMDC110F-2                                       | TYCO                     | miniSMDC110F-2               | E74889,                                                             |
| 1759100002 | (TF)Buzzer.DIP.40mA.85dB P-P=6.5mm.志豐.KCG1206-DS                                          | KINGSTATE                | KCG1206-DS                   | E194246 UL94V-2,                                                    |
| 1759200161 | (TF)CPU Cooler Fan.for LGA775 Pentium4 3.6G.4P.12V.Dual ball bearing.捷豐.LGA-775-959546008 | CMT                      | LGA-775-959546008            | E236658,                                                            |
| 1907910003 | (TF)PCB.IMBA-910.Rev.A1.0.4Layers Green                                                   | EVERLAST WIN             |                              | E216522 V-0                                                         |
| 9657666600 | (TF)Accessory.for All Series Jumper                                                       | CATCH                    | 9657666600                   | E107536(M)                                                          |

| P/N        | DESCRIPTION                                                                                 | MAKER    | PART NO.         | UL NO./ Flame         |
|------------|---------------------------------------------------------------------------------------------|----------|------------------|-----------------------|
| 121110010Y | (TF)COIL.1uH.+-25%.DCR=0.08Ohm.Idc=20A.Wire Size=0.6*3mm*7.5TS.DIP.GOTREND.C5008P-06C07YDPS | GOTREND  | C5008P-06C07YDPS | E218438,              |
| 121110010Z | (TF)Inductor.1uH.10%.SMD.2.4*1.6mm.GOTREND.GNLE2012P-1R0K                                   | GOTREND  | GNLE2012P-1R0K   | E84081,               |
| 16515C0492 | (TF)DDR2 SKT.DIP.240P.FOXCONN.AT24017-H3B-4F                                                | FOXCONN  | AT24017-H3B-4F   | E93750,               |
| 16515C0495 | (TF)DDR2 SKT.DIP.240P.(Blue).FOXCONN.AT24017-                                               | FOXCONN  | AT24017-H3L-4F   | E93750,               |
| 165440910B | (TF)D-SUB CONNECTOR.9P.90D(M).DIP.Green.Astron.DB6A-09-AMGN1-R                              | Astron   | DB6A-09-AMGN1-R  | E59481,               |
| 175011901H | (TF)Lithium                                                                                 | PANASONI | CR2032           | MH12210,              |
| M06880M000 | (TF)Metal.AL.Heat sink.36.8*36*10.1mm.研揚字型(藍色).For BGA Package.捷豐.JF-363602                 | CMT      | JF-363602        | E41938(M)<br>UL94V-2, |