

P/N	DESCRIPTION	MAKER	PART NO.	UL NO./ Flame Class
1211000180	(TF)COIL.1uH.+/- 20%.SMD.7.3*6.8*3.0mm.DCR=9mohm.Irms=11Amp.G OTREND.GSTC063P-1R0MN	GOTREND	GSTC063P- 1R0MN	E84081,
121110100F	(TF)Inductor.10uH.10%.SMD.2.4*1.6mm.GOTREND.GN LE2012P-100K	GOTREND	GNLE2012P- 100K	E84081,
1211103370	(TF)COIL.0.33uH.Irms=20A.Isat=30A.20%.SMD(7.3x6.8 x3.0).2pin.RDC=3.9m Ohm.GOTREND.GSTC063P- R33MN	GOTREND	GSTC063P- R33MN	E218438 / E84081,
16515A0997	(TF)DDR2 SODIMM SKT.SMD.200P.H=6.5mm.1.8V.FOXCONN.AS0A426- N6RN-4F	FOXCONN	AS0A426- N6RN-4F	E93750,
165300420L	(TF)PIN HEADER.4*2P.180D.(M).1.27mm.SMD.W/Cap.Astron.27 -44041-204-2G-TB1R	Astron	27-44041- 204-2G- TB1R	E52579(M) 94V-0,
1653150221	(TF)PCB SKT.50*2P.180D.(F).SMD.HIROSE.FX8-100P- SV(92)	HIROSE	FX8-100P- SV(92)	E109088,
1653930130	(TF)FLAT RIBBON Connector.30*1Pin.Hirose.FH12- 30S-0.5SH(55)	Hirose	FH12-30S- 0.5SH(55)	E52579,E583829,
1907X94512	(TF)PCB.XTX-945GSE.Rev.A1.0.8Layers Blue	K-BRIDGE		E120558